WEST BENGAL POLLUTION CONTROL BOARD

omres(

Paribesh Bhawan' Bldg No. 10A, Block - LA, Sector-III Salt Lake City, Kolkata-700 098

[Renewal]

Consent Letter Number : C.012 S S 19

Memo Number: 01/25/CON (BM)-1633/2003

Date: 05.01.2024

Consent to Operate

under

Section 25 & 26 of the Water (Prevention and Control of Pollution) Act, 1974 and Section 21 of the Air (Prevention and Control of Pollution) Act, 1981

The West Bengal Pollution Control Board (hereinafter referred to as State Board) under the provisions of Section 25 &

The West Benga 26 of the Water (Preven of Pollution) Act, 1981	tion and Control of Po	Ilution) Act, 1974, as a	mended and So	ection 21 of the Air (Pr	Evention and Control
of Pollution) Act, 1981	, as amended and Kui	es and Orders made in	ileditati, ile	7.6	·
Mclieare	Environ	M. Letro M	magama	rent Prt. 6	XII:
	U 0 2220		(Addres	ss of Regd. office/Head	d/Office/City Office)
(hereinafter referred to	as Applicant) for its u	nit located at Al,	f, Roac	1. P.O-H	owrah,
(nerematter referred to	as Applicant) for its u	int tocated at	-36		
P.S- Lit	vals to	Work - 71	1105	Course	
•	The same of the sa	The same of the sa		CO TO THE PARTY OF	
				······································	
	VERIETH !			Detailed address of the	manufacturing unit)
for a period from	late ed	TSS UR	to	30/11/202	- &
	Verilla 1	Commission of the control of the con			
to operate the industrial trial unit, in accordance instance the quantity an	with the conditions	as mentioned in the Ar	nexure to this	consent letter provide	ed on any day at any
the Table I & II of this					

Breach of the conditions and / or failure to comply with the directions as set out in the Annexure shall render the applicant liable for prosecution under the provisions of the Water (Prevention and Control of Pollution) Act, 1974 and Air (Prevention and Control of Pollution) Act, 1981.

The State Board reserve the right to revoke, withdraw or make any reasonable variation / change / alter the conditions of this consent letter giving one month's notice to the applicant.

For and on behalf of the State Board

(Member Secretary/Chief Engr./ Sr. Env. Engr. / Env. Engr. / Asst. Env. Engr.)
Chief Engineer

Bio-Medical W.M.

(Seal)

ANNEXUR	E

7.1 (45)	t Pytimiting
M. and age M.	Orrid
I wiren m leaded [1]	1 . leaberman
Malicox	A STATE OF THE STA
Consent to INTERNATIONAL CONTRACTOR OF THE PARTY CONTR	
41 E Koopland	
for its unit at 11 - P 1110x	
Consent to Malicone Environmental Managem for its unit at 11/1 Road Co- Hewalic P. 5-	

Conditions:

Condition	is Consent is valid for the manufacture of:
01. Th	tis Consent is valid for the manufacture of: Ouantity manufactured per month Ouantity manufactured per month
Sl. No.	1 St Consider products and by-products
01	Common Blomestical Worte Treatment to 200 Capacità Common Blomestical Worte Treatment 1x250 yosten. Capacità Locale del Capacità Incinenter, 1x800 lit Botal
02	1 2 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
03	and 1x 15015 m. (Showers of
04	and 1x 15015 hr. (standbo) capacity Trainenger, 1 x 130 Rithard Capacity Autoclave and Shrobder of Capacity 8918 hr. and 60 Kg/m, Capacity respectively.
05	capacity 8018 ms and 60 Fs/m Capacits
06	
07	
08	
09	The state of the s
10	Manual Manual Property and the lawyer
11	THE STREET STREET
12	CHECK CHARLES EXTENT & EXTENT

- The Applicant shall remain responsible for quantity and quality of liquid effluent and air emissions.
- Daily discharge of industrial liquid effluent shall not exceed 03.
- Daily discharge of domestic liquid effluent shall not exceed
- The Applicant shall discharge liquid effluent tow......(place of discharge)
- throughnos, outlets / outfalls.
- To bring into any altered or new outlet/outfall or to change the place of discharge, the Applicant shall have to inform the Board and obtain prior permission of the Board in this effect.
- The Applicant shall provide comprehensive facility for treatment of industrial liquid waste and domestic liquid waste (sewage, sullage and liquid effluent generated from canteen), and operate and maintain the same continuously so that the quality of final effluent conforms to the Standard as given in Table-I in page 03.

(Member Secretary/Chief Engr./ Sr. Env. Engr. / Env. Engr. / Asst. Env. Engr.)
Chief Engineer

Bio-Medical W.M O.*

Continued.....

	Hall	eare Environmental. Read, P.O-Howral		
	,	Table-I		Enganoman
Outlet No.	Nature of effluent	Parameters	Standard	Frequency of effluent sampling
04	Domertic	pH	Between: 5.5 +0 9.0	newlo
-		Total Suspended Solids Biochemical Oxygen Demand (3day at 27°C)	Not to exceed: /60 mg/l. Not to exceed: 30 mg/l.	Demas
		Chemical Oxygen Demand	Not to exceed: 250 mg/l.	7
		Oil & Grease	Not to exceed: 10 mg/1.	-
Inde	Arial off	went to be recycled at fa	treatment in ET	8
		/ / /		
		ACTION C. M. CONT. Market Co.		
_		A Part in various Application and the	industrial A	
	-	WESTBEN	CAL	
		WE DELIVERY		
		KARATATAN SULUM SULUM SUNTAN SUKATA	TO STANDARD CONTRACTOR	
		PROCESSOR TO DESCRIPTION OF THE PROCESSOR OF THE PROCESSO	go by comments and	
		- CEPTER -		
	-	The state of the s		
				-
		VALUE SELECTION OF THE PARTY OF	The Edward of	
	100	Verification (1) and reading	The second second	
		Constitution of the consti	THE PERSON NAMED IN	
pro Dai	Control of Povisions of the solly water consulations and the sollowing the conference of the control of the con	ereby water gets polluted and the pollutants	ercunder and the Applicant sha ot exceed:-	Il comply with
•	are easily biod	egradable		
•	are easily biod	ereby water gets polluted and the pollutants	→	
The	are easily biod Processing wh are not easily be Applicant sha	ereby water gets polluted and the pollutants	f Water Consumption in the pres	cribed form and
·	are easily biod Processing wh are not easily be Applicant sha	ereby water gets polluted and the pollutants biodegradable Il regularly submit to the Board the Returns of the under Section 3 of the said Act.	f Water Consumption in the pres	cribed form and
The	are easily biod Processing wh are not easily be Applicant sha	ereby water gets polluted and the pollutants biodegradable Il regularly submit to the Board the Returns of the under Section 3 of the said Act.	f Water Consumption in the pres	cribed form and
• The	are easily biod Processing wh are not easily be Applicant sha	ereby water gets polluted and the pollutants biodegradable Il regularly submit to the Board the Returns of the under Section 3 of the said Act.	f Water Consumption in the pres	cribed form and

		۰	•
•	4	1	1

Consent to Medicar and Environment of Management lut. Ly
for its unit at 41. ft. Road P.O - Howah, P.S - Li Push

Howard - 711105

- The Applicant shall install suitable device for measuring the volume of water consumed for different purposes as mentioned above giving correct result to the satisfaction of the State Board.
- All the stacks connected to various sources of emissions must be designated by numbers such as S-1, S-2, S-3, etc., and this must be painted/displayed to faciliate identification.
- 13. The Applicant shall install comprehensive control system consisting of pollution control equipment as is warranted with reference to generation of air emissions and operate and maintain the same continuously so as to achieve the level of pollutants of the Standard as given in Table-II below:

Table-II

				SHEET STREET	to all world by a dis-	WHEEP.				
Stack No.	Stack height from	Stack attached to (sources and control system.	Volume Nm³/hr.	Velocity of gas emission	a		t 92	Correc	tion	Frequency of emission sampling
	GI., (in mts.)	if any):	WE:	m/sec E	SPM (mg/Nm³)	A70 X			Total Disins is & furan	
S-I	30 M	1x150 to ha. (tandles)	ASSESSED AND ASSESSED	50100	400 ms/4m3	FER NW3	malum?	perum3	g Quartedy
S-2	10	D-4 set		OTHER DESIGNATION OF THE PERSON OF THE PERSO	A CHARLES	- Pl	000	= An	Nexure	1>
S-3	/					679kg		1	xi	
S-4			A PARTIES		CONTRACTOR OF THE PARTY OF THE	y en				
S-5		79			No. of the last				th I	
S-6										
S-7										
S-8			8							
S-9										
-10 .						7				101-20D

(Member Secretary/Chief Engr./ Sr. Env. Engr. / Env. Engr. / Asst. Env. Engr.)

Chief Engineer Bio-Medical W.M. Cell

Continued.....

1	(5)
	Consent to Malicone Envisorment of Mornogen ent let to for its unit at 11 E' Road, P. 0 - Howards P. 5 - Li Prote
	Consent to 11 Post of P. O - Howards P. C - I was
	for its unit at 11 10 10 10 10 10 10 10 10 10 10 10 10
	Hzwels - 71) 105

- 14. The Applicant shall provide ports in the stack(s) and other necessary permanent facilities such as ladder, platform, etc. for monitoring/sampling the air emissions and the same shall be made available for inspection and use by the State Board's staff as well as State Board's authorised agencies.
- 15. The Applicant shall observe the following firel consumption pattern:

Sl. No	Type of fuel	Quantity consumed per day	Incine on tors of Da cont
01	TISP	R. 88811	
0.3			
04			Agglacian

16. The Applicant shall maintain the generation and treatment/disposal of non-hazardous solid waste as specified below:-

Type of waste	Quantity	Treatment	Disposal
ETC Studge +	1707.82 Folder	ALCO ALCO ALCO ALCO ALCO ALCO ALCO ALCO	TO NO OFFICER - HAMMES
Autocharabola Som	20 1		Through authorited

17. The Applicant shall take adequate measures for control of noise levels from its own sources within the premises within the limit given below:-

Time	Limit in dB(A) Leq
Day Time (06 a.m. to 09 p.m.)	65
Night Time (09 p.m. to 06 a.m.)	55

- 18. The Applicant shall at all times maintain good house-keeping, proper working order, and operate efficiently for control of pollution from all sources so as not to cause nuisance to surrounding areas/inhabitants and to achieve compliance with the terms and conditions of the consent.
- 19. The Applicant shall bring about at least 33% of the available open land under the green coverage / plantation.
- 20. The Applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by the Applicant to maintain compliance with the terms and conditions of the consent. In absence of such an alternate electric power source, the Applicant shall stop, reduce or otherwise control production to abide by the terms and conditions of the Consent regarding pollution level.
- 21. The Applicant shall install a separate energy meter showing the consumption of energy for operation of pollution control devices.
- 22. The Applicant shall ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises.
- The Applicant shall provide drainage system for conveying industrial and domestic liquid waste. Storm-water drain shall be kept separate from the drainage system meant for industrial and domestic liquid waste

(Member Secretary/Chief Engr./Sr. Env. Engr. / Env. Engr. / Asst. Env. Engr.)

Chief Engineer
Bio-Medical W.M. Ce¹¹ Continued.......

		mant Put I da
M. Nicara	Environmental Manage	N. Sezazi
Consent to Parishal All Comments	1 Pa- Housenhart	5- 1 1000
for its unit at 11.		
	1 1107	
	.L.J. II	chemicals used in pollution condox sy

- 25. The Applicant shall get the samples of hazardous wastes/reachates analysed at John from the laboratory recognised of the West Bengal Pollution Control Board and ensure that they conform to the limits stipulated. Test reports shall be sent to the Board.
- 26. The Applicant shall provide adequate and safe facility for collection of air, waste water and solid waste samples by the State Board's staff as well as State Board's authorised agencies.
- 27. The Applicant shall submit to the State Board by the 30th September of every year the Environmental Statement Report for the financial year ending 31st March of the current year in the prescribed form (Form -V) as required under the provisions of rule 14 of the Environment (Protection) [Second Amendment] rules, 1992.
- 28. The Applicant shall allow the Officers of the State Board to enter into the applicant's premises at any reasonable time to inspect the pollution control systems as well as monitoring and measuring devices in connection with prevention & control of pollution.
- 29. The Applicant shall maintain an Inspection Book in the factory premises which shall be made available to Officers & employees of the State Board for inspection, review and to write down any direction or observation as is deemed necessary during the inspection from time to time.
- The Application shall furnish to the State Board all information in respect of quality, quantity, rate of discharge, place of discharge of liquid effluent and air emissions.
- The Applicant shall maintain adequate number of qualified and trained personnel among his staff for proper maintenance and operation of the effluent treatment and / or emission control devices and for overall environment management of the industry.
- The Applicant shall have to make registration for the use of groundwater if any, with Central Ground Water Authority.
- 33. The Applicant shall intimate to the State Board immediately of any occurrence or apprehension of occurrence of discharge of any poisonous, noxious or pollutants in excess of quality as well as quality as mentioned earlier to any receiving water body/receiving system or to atmosphere owing to accident or other unforeseen incident/event including natural disaster. The Applicant Shall (i) take all steps adequate to prevent such accident discharge/release of poisonous, noxious or pollutants and to limit their consequences to persons and the environment, (ii) provide to the persons working on the site with the information, training and equipment including antidotes necessary to ensure their safety and mitigate the accidental release of poisonous noxious or pollutants to the environment.
- 34. The Applicant shall make an application to the State Board in the prescribed form for renewal of the consent at least -60 (sixty) days before the date of expiry of this Consent.
- The Applicant shall not make any alternation/modification/expansion in the existing manufacturing process and equipment as well as the pollution control system without prior approval of the Board.

36. The Applicant shall comply with the conditions as laid do	wn in the Manufacture, Storage and Import of hazardous
Chemicals Rules, 1989 and Hazardous Wastes (Managem	cut & Handfing) Rules, 1989, 2016 and Its amend front
De The prot should contly with the ferrie I quideline	on & Handing Rules, 1989, 2016 and Its amendments for CBMWIFS published to the CPCB
A ATTION OF THE WORLD COMPANY LATERS	16 - 1/05.01.2024
	/mon 2 - 103. Visa
and also and falls, Lope to the amendments therealth	
Member Secret	rry/Chief Engr./ Sr. Env. Engr. / Env. Court / Photograp Engr.)
03/2=1=10000 11/2017000	18/01/2019 properts. Bio-Medical W.M. Cell
10 35/ 20° 5 20.	18/01/2019 properts. BIO-Medical W.M. Cell

NNEXURE I to 'Consent to Operate' No. .. CO 1288 19

Name of the unit: Medicare Environmental Management Pvt. Ltd. 41, F-Road, Belgachia, P.O: Howrah, P.S: Liluah, Howrah - 711105

- a. For DG set below 800 kW H = $h + 0.2 \times VkVA$ Where H = height of exhaust stack h = height of building.
- b. For DG set above 800 kW Minimum 30 meter. In case building height is more than 30 meter Stack Height = Building height + minimum 6 meter

TABLE

Power Category	Emission Limits (g/kW-hr)			Smoke Limit (light absorption coefficient, m ⁻¹)
	NOx+HC	CO	PM	
lpto 19 KW	≤ 7.5	≤ 3.5	≤ 0.3	≤ 0.7
Jore than 19 KW upto 75	≤ 4.7	≤ 3.5	≤ 0.3	≤ 0.7
(W) Iore than 75 KW upto 800 W	≤ 4.0	≤ 3.5	≤ 0.2	≤ 0.7

EMISSION STANDARDS FOR DIESEL ENGINES (ENGINE RATING MORE THAN 0.8 MW (800 KW)) FOR POWER PLANT, GENERATOR SET APPLICATIONS AND OTHER REQUIREMENTS

TABLE

Parameter		Area	Total engine rating of the plant (includes existing as well as new generator sets)	Generator sets commissioning date			
		Categor y		Before 1.7.2003	Between 1.7.2003 and 1.7.2005	On or after 1. 7. 2005	
			Upto 75 MW	1100	970	710	
NOx (as	NOx (as NO ₂) (AT 15% O ₂), dry basis,		Upto 150 MW	i l			
			More then 75 MW	1100	710	360	
in ppmv		Α	More then 150 MW				
	-732	Both	More men 150 WW	150	100)	
NMHC K	NMHC (as C)(at 15% O ₂), mg/Nm ³		7	,50			
O21, mg/				7.5	75		
PM (at	Diesel Fuels-	Both		1.7			
15%	HSD & LDO	A and B		150			
O2).	Furnace Oils-	Both					
mg/Nm	LSHS & FO	A and B		1			
3		Both		150	150		
CO (at 15	CO (at 15% O ₂),				*10.50 M	- 6	
mg/Nm³ Sulphur Content in fuel		A and B		< 2%			
		A		< 4%			
		В	11-4-51414/	Only Diesel fuels (HSD, LDO) shall be used.			
Fuel specification Fo		For A only	Up to 5MW				
			total la a maximum o	f the follow	ing, in meter	:	
Stack heig generator commissic 1.7.2003)	ght (for sets oned after	Stack height shall be maximum of the following, in meter: (i) 14 Q ^{0.3} , Q= Total SO ₂ emission from the plant in kg/hr. (ii) Minimum 6 m. above the building where generator set is installed. (iii) 30 m.					

Chief Engineer

Bio-medical Waste Management Cell West Bengal Pollution Control Board

Chief Engineer Bio-Medical W.M. C.